



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C09K 5/04, 3/30, A62D 1/00, C11D 7/50, C23G 5/028	A1	(11) International Publication Number: WO 97/28229 (43) International Publication Date: 7 August 1997 (07.08.97)
(21) International Application Number: PCT/US97/01501 (22) International Filing Date: 23 January 1997 (23.01.97) (30) Priority Data: 60/010,941 31 January 1996 (31.01.96) US 08/784,847 15 January 1997 (15.01.97) US (71) Applicant: E.I. DU PONT DE NEMOURS AND COMPANY [US/US]; 1007 Market Street, Wilmington, DE 19898 (US). (72) Inventors: MERCHANT, Abid, Nazarali; 1408 Clive Circle, Wilmington, DE 19803-4703 (US). MINOR, Barbara, Haviland; 233 Green Haven Drive, Elkton, MD 21921-7619 (US). (74) Agent: KING, Karen, K.; E.I. du Pont de Nemours and Company, Legal/Patent Records Center, 1007 Market Street, Wilmington, DE 19898 (US).		(81) Designated States: JP, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: NONAFLUOROMETHOXYBUTANE COMPOSITIONS		
(57) Abstract Compositions of nonafluoromethoxybutane and at least one component selected from the group consisting of methanol, ethanol, isopropanol, n-heptane, trans-1,2-dichloroethylene, cis-1,2-dichloroethylene and acetone, and 1,1,1,2,3,4,4,5,5,5-decafluoropentane are described. These compositions are useful as cleaning agents, displacement drying agents, refrigerants, heat transfer media, expansion agents for polyolefins and polyurethanes, aerosol propellants, gaseous dielectrics, fire extinguishing agents, power cycle working fluids, polymerization media, particulate removal fluids, carrier fluids, and buffing abrasive agents.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

TITLE

NONAFLUOROMETHOXYBUTANE COMPOSITIONS

FIELD OF THE INVENTION

5 This invention relates to compositions containing
nonafluoromethoxybutane. These compositions are useful as cleaning agents,
displacement drying agents, refrigerants, heat transfer media, expansion agents for
polyolefins and polyurethanes, aerosol propellants, gaseous dielectrics, power cycle
working fluids, fire extinguishing agents, polymerization media, particulate removal fluids,
10 carrier fluids, and buffing abrasive agents.

BACKGROUND OF THE INVENTION

Fluorinated hydrocarbons have many uses such as cleaning agents or
refrigerants. Such compounds include trichlorofluoromethane (CFC-11) and 1,1,2-
15 trichloro-1,2,2-trifluoroethane (CFC-113).

In recent years it has been pointed out that certain kinds of fluorinated
hydrocarbon compounds released into the atmosphere may adversely affect the
stratospheric ozone layer. Although this proposition has not yet been completely
established, there is a movement toward the control of the use and the production of
20 certain chlorofluorocarbons (CFCs) and hydrochlorofluorocarbons (HCFCs) under an
international agreement.

Accordingly, there is a demand for the development of new compounds
that have a lower ozone depletion potential than existing compounds while still achieving
an acceptable performance in cleaning agent and refrigeration applications.

25 In refrigeration applications, a refrigerant is often lost during operation
through leaks in shaft seals, hose connections, soldered joints and broken lines. In
addition, the refrigerant may be released to the atmosphere during maintenance procedures
on refrigeration equipment. If the refrigerant is not a pure component or an azeotropic or
azeotrope-like composition, the refrigerant composition may change when leaked or
30 discharged to the atmosphere from the refrigeration equipment, which may cause the
refrigerant to become flammable or to have poor refrigeration performance.

Accordingly, it is desirable, if possible, to use as a refrigerant a single
compound or an azeotropic or azeotrope-like composition of more than one compound.

It is also desirable to find replacements for CFCs and HCFCs for use as a
35 cleaning agent or solvent to clean, for example, electronic circuit boards. Electronic
components are soldered to circuit boards by coating the entire circuit side of the board

5 nonflammability, low toxicity, and high solvency power so that flux and flux-residues can
be removed without damaging the substrate being cleaned. Further, it is desirable that
cleaning agents that include a fluorinated hydrocarbon be azeotropic or azeotrope-like so
that they do not tend to fractionate upon boiling or evaporation. If the cleaning agent
10 were not azeotropic or azeotrope-like, the more volatile components of the cleaning agent
would preferentially evaporate, and the cleaning agent could become flammable or could
have less-desirable solvency properties, such as lower rosin flux solvency and lower
inertness toward the electrical components being cleaned. The azeotropic property is also
desirable in vapor degreasing operations because the cleaning agent is generally redistilled
15 and reused for final rinse cleaning.

Replacements for CFCs and HCFCs may also be useful as heat transfer media
to transfer heat from a heat source to a heat sink, blowing agents in the manufacture of
closed-cell polyurethane, phenolic and thermoplastic foams, as propellants in aerosols,
gaseous dielectrics, fire extinguishing agents, power cycle working fluids such as for heat
20 pumps, inert media for polymerization reactions, fluids for removing particulates from
metal surfaces, as carrier fluids that may be used, for example, to place a fine film of
lubricant on metal parts, as buffing abrasive agents to remove buffing abrasive compounds
from polished surfaces such as metal, as displacement drying agents for removing water,
such as from jewelry or metal parts, as resist developers in conventional circuit
25 manufacturing techniques including chlorine-type developing agents, or as strippers for
photoresists when used with, for example, a chlorohydrocarbon such as 1,1,1-
trichloroethane or trichloroethylene.

Accordingly, it has been found that compositions containing
nonafluoromethoxybutane have a lower ozone depletion potential and are suitable cleaning
30 agents, displacement drying agents, refrigerants, heat transfer media, expansion agents for
polyolefins and polyurethanes, aerosol propellants, gaseous dielectrics, power cycle
working fluids, fire extinguishing agents, polymerization media, particulate removal fluids,
carrier fluids, and buffing abrasive agents.

SUMMARY OF THE INVENTION

The present invention relates to compositions of nonafluoromethoxybutane and at least one of the following components: methanol, ethanol, isopropanol, n-heptane, trans-1,2-dichloroethylene, cis-1,2-dichloroethylene, acetone, and 1,1,1,2,3,4,4,5,5,5-decafluoropentane.

The present invention also relates to the following binary compositions: a first component, nonafluoromethoxybutane and a second component, wherein the second component is selected from the group consisting of methanol, ethanol, isopropanol, n-heptane, trans-1,2-dichloroethylene, cis-1,2-dichloroethylene and acetone.

The present invention also relates to the following ternary compositions: nonafluoromethoxybutane, n-heptane, and a third component, wherein the third component is selected from the group consisting of methanol, ethanol or isopropanol; nonafluoromethoxybutane, trans-1,2-dichloroethylene and a third component, wherein the third component is methanol, ethanol or isopropanol; nonafluoromethoxybutane, cis-1,2-dichloroethylene and a third component, wherein the third component is methanol or ethanol; and nonafluoromethoxybutane, acetone and a third component, wherein the third component is methanol, ethanol, or isopropanol; nonafluoromethoxybutane, 1,1,1,2,3,4,4,5,5-decafluoropentane and methanol.

These compositions are useful as cleaning agents, displacement drying agents, refrigerants, cleaning agents, expansion agents for polyolefins and polyurethanes, aerosol propellants, heat transfer media, gaseous dielectrics, power cycle working fluids, polymerization media, particulate removal fluids, fire extinguishants, carrier fluids, and buffing abrasive agents.

Further, the invention relates to the discovery of binary azeotropic or azeotrope-like compositions comprising effective amounts of these components to form an azeotropic or azeotrope-like composition.

DETAILED DESCRIPTION

The present invention relates to compositions of nonafluoromethoxybutane and at least one of the following components: methanol, ethanol, isopropanol, n-heptane, trans-1,2-dichloroethylene, cis-1,2-dichloroethylene, acetone, and 1,1,1,2,3,4,4,5,5,5-decafluoropentane.

The present invention also relates to the discovery of binary compositions of nonafluoromethoxybutane ($C_4F_9OCH_3$) and methanol, ethanol, isopropanol, n-heptane, trans-1,2-dichloroethylene (t-DCE), cis-1,2-dichloroethylene (c-DCE), or acetone; and ternary compositions of $C_4F_9OCH_3$, n-heptane and methanol, ethanol, or isopropanol;

methanol or ethanol, $C_4F_9OCH_3$, acetone, $C_4F_9OCH_3$, 1,1,1,2,3,4,4,5,5,5-decafluoropentane (HFC-43-10mee) and methanol. 1-99 wt.% of each of the components in the above compositions can be used as cleaning agents, displacement drying agents, refrigerants, expansion agents for polyolefins and polyurethanes, aerosol propellants, heat transfer media, gaseous dielectrics, fire extinguishants, power cycle working fluids, polymerization media, particulate removal fluids, carrier fluids, and buffing abrasive agents.

The present invention also relates to the discovery of azeotropic or azeotrope-like compositions of effective amounts of $C_4F_9OCH_3$ and methanol, ethanol, isopropanol, n-heptane, t-DCE, c-DCE, or acetone; $C_4F_9OCH_3$, n-heptane and methanol, ethanol or isopropanol; $C_4F_9OCH_3$, t-DCE and methanol, ethanol or isopropanol; $C_4F_9OCH_3$, c-DCE and methanol or ethanol; $C_4F_9OCH_3$, acetone and methanol, ethanol, or isopropanol; $C_4F_9OCH_3$, HFC-43-10mee and methanol to form an azeotropic or azeotrope-like composition.

Nonafluoromethoxybutane ($C_4F_9OCH_3$) isomers of the present invention include 1,1,1,3,3,3-hexafluoro-2-methoxy-2-(trifluoromethyl)-propane ($CH_3OC(CF_3)_3$), 1,1,1,2,2,3,3,4,4-nonafluoro-4-methoxy-butane ($CH_3OCF_2CF_2CF_2CF_3$), 1,1,1,2,3,3,3-hexafluoro-2-(trifluoromethyl)-3-methoxy-propane ($CH_3OCF_2CF(CF_3)_2$), and 1,1,1,2,3,3,4,4,4-nonafluoro-2-methoxybutane ($CH_3OCF(CF_3)CF_2CF_3$) with approximate isomer boiling points of 60°C. Other components of the compositions of the present invention include the following:

1. methanol (CH_3OH), boiling point = 65°C
2. ethanol (CH_3CH_2OH), boiling point = 78°C
3. isopropanol ($(CH_3)_2CHOH$), boiling point = 82°C
4. n-heptane ($CH_3(CH_2)_5CH_3$), boiling point = 98°C
5. trans-1,2-dichloroethylene ($CHCl=CHCl$), boiling point = 48°C
6. cis-1,2-dichloroethylene ($CHCl=CHCl$), boiling point = 60°C
7. acetone, (CH_3COCH_3), boiling point = 56°C
8. 1,1,1,2,3,4,4,5,5,-decafluoropentane, ($CF_3CHFCHFCF_2CF_3$), boiling point = 54.6°C

By "azeotropic" composition is meant a constant boiling liquid admixture of two or more substances that behaves as a single substance. One way to characterize an azeotropic composition is that the vapor produced by partial evaporation or distillation of the liquid has the same composition as the liquid from which it was evaporated or distilled, that is, the admixture distills/refluxes without compositional change. Constant boiling

compositions are characterized as azeotropic because they exhibit either a maximum or minimum boiling point, as compared with that of the non-azeotropic mixtures of the same components.

By "azeotrope-like" composition is meant a constant boiling, or
5 substantially constant boiling, liquid admixture of two or more substances that behaves as a single substance. One way to characterize an azeotrope-like composition is that the vapor produced by partial evaporation or distillation of the liquid has substantially the same composition as the liquid from which it was evaporated or distilled, that is, the admixture distills/refluxes without substantial composition change. Another way to
10 characterize an azeotrope-like composition is that the bubble point vapor pressure and the dew point vapor pressure of the composition at a particular temperature are substantially the same.

It is recognized in the art that a composition is azeotrope-like if, after 50 weight percent of the composition is removed such as by evaporation or boiling off, the
15 difference in vapor pressure between the original composition and the composition remaining after 50 weight percent of the original composition has been removed is less than 10 percent, when measured in absolute units. By absolute units, it is meant measurements of pressure and, for example, psia, atmospheres, bars, torr, dynes per square centimeter, millimeters of mercury, inches of water and other equivalent terms well
20 known in the art. If an azeotrope is present, there is little difference in vapor pressure between the original composition and the composition remaining after 50 weight percent of the original composition has been removed.

Therefore, included in this invention are compositions of effective amounts of $C_4F_9OCH_3$, methanol, ethanol, isopropanol, n-heptane, t-DCE, c-DCE, or acetone;
25 $C_4F_9OCH_3$, n-heptane and methanol, ethanol, or isopropanol; $C_4F_9OCH_3$, t-DCE and methanol, ethanol or isopropanol; $C_4F_9OCH_3$, c-DCE and methanol or ethanol; $C_4F_9OCH_3$, acetone and methanol, ethanol or isopropanol; $C_4F_9OCH_3$, HFC-43-10mee and methanol such that after 50 weight percent of an original composition is evaporated or boiled off to produce a remaining composition, the difference in the vapor pressure
30 between the original composition and the remaining composition is 10 percent or less.

For compositions that are azeotropic, there is usually some range of compositions around the azeotrope point that, for a maximum boiling azeotrope, have boiling points at a particular pressure higher than the pure components of the composition at that pressure and have vapor pressures at a particular temperature lower than the pure
35 components of the composition at that temperature, and that, for a minimum boiling azeotrope, have boiling points at a particular pressure lower than the pure components of

10 The range of compositions that have a maximum or minimum boiling point
 at a particular pressure, or a maximum or minimum vapor pressure at a particular
 temperature, may or may not be coextensive with the range of compositions that have a
 change in vapor pressure of less than about 10% when 50 weight percent of the
 composition is evaporated. In those cases where the range of compositions that have
 maximum or minimum boiling temperatures at a particular pressure, or maximum or
 minimum vapor pressures at a particular temperature, are broader than the range of
 15 compositions that have a change in vapor pressure of less than about 10% when 50 weight
 percent of the composition is evaporated, the unexpected intermolecular forces are
 nonetheless believed important in that the refrigerant compositions having those forces
 that are not substantially constant boiling may exhibit unexpected increases in the capacity
 or efficiency versus the components of the refrigerant composition.

20 The components of the compositions of this invention have the following
 vapor pressures:

		25°C	50°C	75°C	100°C	110°C
	<u>Component</u>	<u>Psia</u>	<u>Psia</u>	<u>Psia</u>	<u>Psia</u>	<u>Psia</u>
25	C ₄ F ₉ OCH ₃	4.07	10.47	23.56	47.52	61.32
	Methanol	2.33	7.71	20.93	48.85	66.20
	Ethanol	1.14	4.26	12.82	32.66	45.67
	Isopropanol	0.82	3.42	10.91	28.70	40.44
	n-Heptane	0.88	2.74	6.99	15.39	20.39
30	t-DCE	6.41	15.88	33.94	64.71	81.59
	c-DCE	3.91	10.30	23.14	45.98	58.84
	Acetone	4.45	11.85	26.79	53.40	68.36

35 Substantially constant boiling, azeotropic or azeotrope-like compositions of
 this invention comprise the following at the temperature specified:

	<u>COMPONENTS</u>	T(°C)	WEIGHT RANGES	PREFERRED
			(wt. %/wt. %)	(wt. %/wt. %)
5	C ₄ F ₉ OCH ₃ /methanol	25	82-99/1-18	92-99/1-8
	C ₄ F ₉ OCH ₃ /ethanol	75	75-99/1-25	90-99/1-10
	C ₄ F ₉ OCH ₃ /isopropanol	100	64-99/1-36	85-99/1-15
	C ₄ F ₉ OCH ₃ /n-heptane	50	71-99/1-29	90-99/1-10
	C ₄ F ₉ OCH ₃ /t-DCE	25	31-78/22-69	40-70/30-60
10	C ₄ F ₉ OCH ₃ /c-DCE	25	44-85/15-56	55-75/25-45
	C ₄ F ₉ OCH ₃ /acetone	25	1-99/1-99	60-99/1-40
	C ₄ F ₉ OCH ₃ /n-heptane/methanol	25	80-99/0.5-18/0.5-19	90-99/0.5-10/0.5-10
	C ₄ F ₉ OCH ₃ /n-heptane/ethanol	75	75-99/0.5-24/0.5-24	88-99/0.5-12/0.5-10
	C ₄ F ₉ OCH ₃ /n-heptane/isopropanol	100	70-99/0.5-29/0.5-29	82-99/0.5-12/0.5-12
15	C ₄ F ₉ OCH ₃ /t-DCE/methanol	25	20-74/24-75/0.5-12	30-60/30-60/0.5-10
	C ₄ F ₉ OCH ₃ /t-DCE/ethanol	100	28-74/24-70/0.1-12	30-60/30-60/0.1-8
	C ₄ F ₉ OCH ₃ /t-DCE/isopropanol	41	29-70/29-70/0.1-12	35-65/30-60/0.1-8
	C ₄ F ₉ OCH ₃ /c-DCE/methanol	25	39-82/16-59/0.1-12	45-70/25-50/0.1-8
	C ₄ F ₉ OCH ₃ /c-DCE/ethanol	110	41-80/19-58/0.1-14	45-70/25-50/0.1-10
20	C ₄ F ₉ OCH ₃ /acetone/methanol	25	0.5-99/0.5-99/0.5-40	40-99/0.5-50/0.5-20
	C ₄ F ₉ OCH ₃ /acetone/ethanol	75	0.5-99/0.5-99/0.5-30	40-99/0.5-50/0.5-15
	C ₄ F ₉ OCH ₃ /acetone/isopropanol	75	0.5-99/0.5-99/0.5-30	40-99/0.5-50/0.5-15
	C ₄ F ₉ OCH ₃ /HFC-43-10-mee/methanol	47	20-75/20-70/0.5-15	30-60/30-60/0.5-10

For purposes of this invention, "effective amount" is defined as the amount of each component of the inventive compositions which, when combined, results in the formation of an azeotropic or azeotrope-like composition. This definition includes the amounts of each component, which amounts may vary depending on the pressure applied to the composition so long as the azeotropic or azeotrope-like compositions continue to exist at the different pressures, but with possible different boiling points.

Therefore, effective amount includes the amounts, such as may be expressed in weight percentages, of each component of the compositions of the instant invention which form azeotropic or azeotrope-like compositions at temperatures or pressures other than as described herein.

For the purposes of this discussion, azeotropic or constant-boiling is intended to mean also essentially azeotropic or essentially-constant boiling. In other words, included within the meaning of these terms are not only the true azeotropes

exhibit essentially equivalent properties for refrigeration and condensation, will also exhibit essentially equivalent properties to the true azeotropic composition in terms of constant boiling characteristics or tendency not to segregate or fractionate on boiling.

10 It is possible to characterize, in effect, a constant boiling admixture which may appear under many guises, depending upon the conditions chosen, by any of several criteria:

- 15 * The composition can be defined as an azeotrope of A, B, C (and D...) since the very term "azeotrope" is at once both definitive and limitative, and requires that effective amounts of A, B, C (and D...) for this unique composition of matter which is a constant boiling composition.
- 20 * It is well known by those skilled in the art, that, at different pressures, the composition of a given azeotrope will vary at least to some degree, and changes in pressure will also change, at least to some degree, the boiling point temperature. Thus, an azeotrope of A, B, C (and D...) represents a unique type of relationship but with a variable composition which depends on temperature and/or pressure. Therefore, compositional ranges, rather than fixed compositions, are often used to define azeotropes.
- 25 * The composition can be defined as a particular weight percent relationship or mole percent relationship of A, B, C (and D...), while recognizing that such specific values point out only one particular relationship and that in actuality, a series of such relationships, represented by A, B, C (and D...) actually exist for a given azeotrope, varied by the influence of pressure.
- 30 * An azeotrope of A, B, C (and D...) can be characterized by defining the compositions as an azeotrope characterized by a boiling point at a given pressure, thus giving identifying characteristics without unduly limiting the scope of the invention by a specific numerical composition, which is limited by and is only as accurate as the analytical equipment available.

35 The azeotrope or azeotrope-like compositions of the present invention can be prepared by any convenient method including mixing or combining the desired

amounts. A preferred method is to weigh the desired component amounts and thereafter combine them in an appropriate container.

Specific examples illustrating the invention are given below. Unless otherwise stated ther in, all percentages are by weight. It is to be understood that these examples are merely illustrative and in no way are to be interpreted as limiting the scope of the invention. In the following Examples, 1,1,1,3,3,3-hexafluoro-2-methoxy2-(trifluoromethyl)-propane was used. However, all isomers of $C_4F_9OCH_3$ are believed to provide similar results.

EXAMPLE 1

A solution containing 94.9 weight percent $C_4F_9OCH_3$ and 5.1 weight percent isopropanol was prepared in a suitable container and mixed thoroughly. The solution was distilled in a five plate Oldershaw distillation column using a 10:1 reflux to take-off ratio. Head and pot temperatures were read directly to $1^\circ C$. The pressure was 756.46 mmHg. Distillate compositions were determined by gas chromatography. Results obtained are summarized in Table 1.

TABLE 1

Cuts	Temp $^\circ C$	Wt% Distilled or Recovered	Weight Percentages	
	Head		$C_4F_9OCH_3$	Isopropanol
1	54	9.7	93.9	6.1
2	55	19.2	93.9	6.1
3	55	28.9	93.9	6.1
4	55	38.5	93.9	6.1
5	55	48.3	93.9	6.1
6	55	58.2	93.9	6.1
7	55	68.0	93.9	6.1
8	55	77.6	94.3	5.7
HEEL	--	92.1	99.3	0.7

Analysis of the above data indicate very small differences between head temperatures and distillate compositions as the distillation progressed. A statistical analysis of the data indicates that the true binary azeotrope of $C_4F_9OCH_3$ and isopropanol has the following characteristics at atmospheric pressure (99 percent confidence limits):

A solution containing 47.5 weight percent $C_4F_9OCH_3$ and 1.7 weight percent methanol was prepared in a suitable container and mixed thoroughly. The solution was distilled in a five plate Oldershaw distillation column using a 10:1 reflux to take-off ratio. Head and pot temperatures were read directly to $1^\circ C$. The pressure was 758.23 mmHg. Distillate compositions were determined by gas chromatography. Results obtained are summarized in Table 2.

TABLE 2

15	Cuts	Temp $^\circ C$	Wt% Distilled	$C_4F_9OCH_3$	Weight	Percentages
		Head	or Recovered		t-DCE	Methanol
	1	36	9.5	54.1	41.0	4.9
	2	36	19.0	53.8	41.1	5.0
	3	38	28.9	53.7	41.5	4.8
20	4	41	38.8	54.3	44.5	1.1
	5	41	48.9	54.9	45.0	0.03
	6	41	59.4	54.8	45.2	ND
	7	41	69.8	54.2	45.8	ND
	8	41	80.7	54.6	45.4	ND
25	HEEL	--	91.0	37.8	62.2	ND

Analysis of the above data indicate very small differences between head temperatures and distillate compositions early in the distillation before the methanol was depleted. This is an indication of a ternary azeotrope between $C_4F_9OCH_3$ /t-DCE and methanol. Data later in the distillation indicate a binary azeotrope between $C_4F_9OCH_3$ and t-DCE. A statistical analysis of the data indicates that the true azeotropes of have the following characteristics at atmospheric pressure (99 percent confidence limits):

$C_4F_9OCH_3$	=	53.9 +/- 0.6
t-DCE	=	41.2 +/- 0.9
Methanol	=	4.9 +/- 0.4
Boiling Pt, °C	=	36.7 +/- 3.5

5

$C_4F_9OCH_3$	=	54.6 +/- 1.0
t-DCE	=	45.4 +/- 1.0
Boiling Pt, °C	=	41.0 +/- 0.5

10

EXAMPLE 3

A solution containing 55.0 weight percent $C_4F_9OCH_3$, 40.0 weight percent trans-1,2-dichloroethylene and 5.0 weight percent isopropanol was prepared in a suitable container and mixed thoroughly. The solution was distilled in a five plate Oldershaw distillation column using a 10:1 reflux to take-off ratio. Head and pot temperatures were read directly to 1°C. The pressure was 764.23 mmHg. Distillate compositions were determined by gas chromatography. Results obtained are summarized in Table 3.

15

TABLE 3

20	Cuts	Temp °C Head	Wt% Distilled or Recovered	$C_4F_9OCH_3$	Weight t-DCE	Percentages Isopropanol
	1	41	9.9	51.8	46.9	1.3
	2	41	20.1	52.0	46.7	1.3
	3	41	30.3	52.0	46.6	1.3
25	4	41	40.2	52.1	46.5	1.4
	HEEL	--	91.6	61.8	5.2	33.0

Analysis of the above data indicate very small differences between head temperatures and distillate compositions as the distillation progressed. A statistical analysis of the data indicates that the true ternary azeotrope of $C_4F_9OCH_3$, t-DCE and isopropanol has the following characteristics at atmospheric pressure (99 percent confidence limits):

30

A solution containing 40.0 weight percent $C_4F_9OCH_3$, 50.0 weight percent HFC-43-10mee and 10.0 weight percent methanol was prepared in a suitable container and mixed thoroughly. The solution was distilled in a five plate Oldershaw distillation column using a 10:1 reflux to take-off ratio. Head and pot temperatures were read directly to $1^\circ C$. The pressure was 759.30 mmHg. Distillate compositions were determined by gas chromatography. Results obtained are summarized in Table 4.

TABLE 4

Cuts	Temp $^\circ C$	Wt% Distilled or Recovered	$C_4F_9OCH_3$	Weight	Percentages
	Head			43-10mee	Methanol
1	46	10.8	42.0	51.2	6.8
2	46	21.0	43.6	49.4	7.0
3	47	31.0	44.9	48.0	7.1
4	47	40.9	45.7	47.2	7.1
5	47	51.0	45.7	47.1	7.2
6	47	61.1	44.7	48.0	7.3
HEEL	--	91.9	16.7	51.5	31.7

Analysis of the above data indicate very small differences between head temperatures and distillate compositions as the distillation progressed. A statistical analysis of the data indicates that the true ternary azeotrope of $C_4F_9OCH_3$, HFC-43-10mee and methanol has the following characteristics at atmospheric pressure (99 percent confidence limits):

$C_4F_9OCH_3$	=	44.9 +/- 2.6
HFC-43-10mee	=	48.0 +/- 2.8
Methanol	=	7.1 +/- 0.4
Boiling Pt, $^\circ C$	=	46.8 +/- 1.3

EXAMPLE 5

A solution containing 40.0 weight percent $C_4F_9OCH_3$, and 15.7 weight percent acetone was prepared in a suitable container and mixed thoroughly. The solution was distilled in a five plate Oldershaw distillation column using a 10:1 reflux to take-off ratio. Head and pot temperatures were read directly to 1°C. The pressure was 757.40 mmHg. Distillate compositions were determined by gas chromatography. Results obtained are summarized in Table 5.

TABLE 5

10

<u>Cuts</u>	Temp °C <u>Head</u>	Wt% Distilled <u>or Recovered</u>	Weight <u>$C_4F_9OCH_3$</u>	Percentages <u>Acetone</u>
1	50	8.9	73.8	26.2
2	51	17.9	72.6	27.4
15 3	51	26.9	73.7	26.3
4	51	36.1	74.6	25.4
HEEL	--	92.9	99.5	0.5

Analysis of the above data indicate very small differences between head temperatures and distillate compositions as the distillation progressed. A statistical analysis of the data indicates that the true ternary azeotrope of $C_4F_9OCH_3$ and acetone has the following characteristics at atmospheric pressure (99 percent confidence limits):

$C_4F_9OCH_3$ = 73.6 +/- 2.5
 25 Acetone = 26.4 +/- 2.5
 Boiling Pt, °C = 50.7 +/- 1.5

EXAMPLE 6

A suitable container was filled with mixtures shown in Table 5 and heated to the boiling point. Stainless steel nuts and bolts coated with various residues were suspended in the container for 10 seconds then removed and observed. Results are reported in Table 5. Solubilities of each mixture with each residue are also shown.

10	T-DCE/ Methanol (54/43.5/2.5) -Solubility	Removed Up to 10%	Removed Up to 50%	Removed Up to 50%	Removed Up to 1%
15	C ₄ F ₉ OCH ₃ / t-DCE/ Isopropanol (52/46.5/1.5) -Solubility	100% Removed Up to 10%	100% Removed Up to 50%	100% Removed Up to 50%	100% Removed Up to 1%
20	C ₄ F ₉ OCH ₃ / HFC-43-10mee Methanol (45/48/7) -Solubility	100% Removed Up to 40%	98% Removed Up to 1%	95% Removed None	90% Removed None
25	C ₄ F ₉ OCH ₃ / Acetone (85/15) -Solubility	100% Removed Up to 50%	100% Removed Up to 1%	100% Removed Up to 1%	95% Removed None
30					

Analysis of the above data indicate these mixtures remove significant amounts of residue and have some solubility in the residues tested. C₄F₉OCH₃/t-DCE/Methanol (54/43.5/2.5) and C₄F₉OCH₃/t-DCE/Isopropanol (52/46.5/1.5) also removed 100% of Alpha 611F RMA flux at room temperature.

EXAMPLE 7

Phase Study

A phase study shows the following compositions are azeotropic at the
 5 temperature specified:

<u>Composition</u>	<u>Weight Percents</u>	<u>Vapor Press.</u>		
		<u>psia</u>	<u>kPa</u>	<u>T(°C)</u>
C ₄ F ₉ OCH ₃ /methanol	97.1/2.9	4.21	29.0	25
C ₄ F ₉ OCH ₃ /ethanol	98.0/2.0	23.71	163	75
10 C ₄ F ₉ OCH ₃ /n-heptane	97.0/3.0	10.56	72.8	50
C ₄ F ₉ OCH ₃ /c-DCE	68.9/31.1	7.00	48.3	25
C ₄ F ₉ OCH ₃ /n-heptane/methanol	93.2/3.4/3.4	4.25	29.3	25
C ₄ F ₉ OCH ₃ /n-heptane/ethanol	92.0/5.2/2.8	24.11	166	75
C ₄ F ₉ OCH ₃ /n-heptane/isopropanol	89.1/5.5/5.4	49.26	340	100
15 C ₄ F ₉ OCH ₃ /t-DCE/ethanol	54.4/44.7/0.9	87.56	604	100
C ₄ F ₉ OCH ₃ /c-DCE/methanol	66.0/32.6/1.4	7.05	48.6	25
C ₄ F ₉ OCH ₃ /c-DCE/ethanol	66.3/32.8/0.9	98.76	681	110

EXAMPLE 8

20 Impact of Vapor Leakage on Vapor Pressure

A vessel is charged with an initial composition at a specified temperature, and the vapor pressure of the composition is measured. The composition is allowed to leak from the vessel, while the temperature is held constant at the temperature specified,
 25 until 50 weight percent of the initial composition is removed, at which time the vapor pressure of the composition remaining in the vessel is measured. The results are summarized below.

	Refrigerant	0 wt% evaporated		50 wt% evaporated		%
30	<u>Weight Percent</u>	<u>Psia</u>	<u>kPa</u>	<u>Psia</u>	<u>kPa</u>	<u>Change</u>
	C ₄ F ₉ OCH ₃ /methanol (25°C)					
	97.1/2.9	4.21	29.0	4.21	29.0	0.0
	99/1	4.16	28.7	4.15	28.6	0.2
35	90/10	4.05	27.9	3.92	27.0	3.2
	82/18	3.80	26.2	3.43	23.6	9.7

	81/19	3.77	26.0	3.37	23.2	10.6
	$C_4F_9OCH_3$ /ethanol (75°C)					
	98.0/2.0	23.71	163	23.71	163	0.0
5	99/1	23.67	163	23.67	163	0.0
	90/10	22.90	158	22.50	155	1.7
	80/20	21.50	148	20.04	138	6.8
	75/25	20.84	144	18.77	129	9.9
	74/26	20.71	143	18.53	128	10.5
10	$C_4F_9OCH_3$ /isopropanol (100°C)					
	94.9/5.1	48.47	334	48.47	334	0.0
	99/1	47.92	330	47.87	330	0.1
	80/20	46.28	319	44.94	310	2.9
15	70/30	44.25	305	41.21	284	6.9
	64/36	43.01	297	38.86	268	9.6
	63/37	42.81	295	38.47	265	10.1
	$C_4F_9OCH_3$ /n-heptane (50°C)					
20	97.0/3.0	10.56	72.8	10.56	72.8	0.0
	99/1	10.52	72.5	10.52	72.5	0.0
	90/10	10.38	71.6	10.26	70.7	1.2
	80/20	9.99	68.9	9.54	65.8	4.5
	71/29	9.68	66.7	8.74	60.3	9.7
25	70/30	9.64	66.5	8.61	59.4	10.7
	$C_4F_9OCH_3$ /t-DCE (25°C)					
	53.9/46.1	8.76	60.4	8.76	60.4	0.0
	60/40	8.75	60.3	8.73	60.2	0.2
30	70/30	8.69	59.9	8.47	58.4	2.5
	78/22	8.54	58.9	7.70	53.1	9.8
	79/21	8.50	58.6	7.53	51.9	11.4
	40/60	8.74	60.3	8.65	59.6	1.0
	32/68	8.70	60.0	8.07	55.6	7.2
35	31/69	8.70	60.0	7.85	54.1	9.8

C ₄ F ₉ OCH ₃ /c-DCE (25°C)						
	68.9/31.1	7.00	48.3	7.00	48.3	0.0
	80/20	6.96	48.0	6.82	47.0	2.0
	85/15	6.89	47.5	6.34	43.7	8.0
5	86/14	6.86	47.3	6.16	42.5	10.2
	50/50	6.97	48.1	6.91	47.6	0.9
	44/56	6.96	48.0	6.51	44.9	6.5
	43/57	6.96	48.0	5.88	40.5	15.5
10 C ₄ F ₉ OCH ₃ /acetone (25°C)						
	84.3/15.7	3.86	26.6	3.86	26.6	0.0
	92/8	3.90	26.9	3.90	26.9	0.0
	99/1	4.03	27.8	4.03	27.8	0.0
	70/30	3.93	27.1	3.91	27.0	0.5
15	50/50	4.10	28.3	4.06	28.0	1.0
	40/60	4.19	28.9	4.14	28.5	1.2
	20/80	4.34	29.9	4.30	29.6	0.9
	1/99	4.44	30.6	4.44	30.6	0.0
20 C ₄ F ₉ OCH ₃ /n-heptane/methanol (25°C)						
	93.2/3.4/3.4	4.25	29.3	4.25	29.3	0.0
	99/0.5/0.5	4.13	28.5	4.12	28.4	0.2
	90/5/5	4.23	29.2	4.22	29.1	0.2
	90/1/9	4.11	28.3	4.00	27.6	2.7
25	90/9/1	4.12	28.4	4.04	27.9	1.9
	85/10/5	4.19	28.9	4.16	28.7	0.7
	85/5/10	4.12	28.4	4.06	28.0	1.5
	85/14/1	4.04	27.9	3.90	26.7	3.5
	85/1/14	3.96	27.3	3.70	25.5	6.6
30	80/10/10	4.10	28.3	4.02	27.7	2.0
	70/15/15	3.94	27.2	3.76	25.9	4.6
	80/1/19	3.81	26.3	3.39	23.4	11.0
	80/2/18	3.87	26.7	3.48	24.0	10.1
	80/19/1	3.98	27.4	3.76	25.9	5.5

35

C₄F₉OCH₃/n-heptane/ethanol (75°C)

	92.0/5.2/2.8	24.11	166	24.11	166	0.0
	99/0.5/0.5	23.71	163	23.69	163	0.1
	80/14/6	23.67	163	23.45	162	0.9
5	80/1/19	21.85	151	20.43	141	6.5
	80/19/1	23.14	160	22.36	154	3.4
	75/15/10	23.29	161	22.93	158	1.5
	75/1/24	21.18	146	19.15	132	9.6
	75/24/1	22.77	157	21.57	149	5.3

10

C₄F₉OCH₃/n-heptane/isopropanol (100°C)

	89.1/5.5/5.4	49.26	340	49.26	340	0.0
	99/0.5/0.5	47.91	330	47.85	330	0.1
	89/10/1	48.25	333	47.93	330	0.7
15	89/1/10	48.37	334	48.13	332	0.5
	80/10/10	48.76	336	48.53	335	0.5
	80/1/19	46.76	322	45.50	314	2.7
	80/19/1	46.91	323	45.39	313	3.2
	70/15/15	47.62	323	45.39	313	3.2
20	70/1/29	44.73	308	41.79	288	6.6
	70/29/1	45.37	313	41.75	288	8.0

C₄F₉OCH₃/t-DCE/methanol (25°C)

	49.5/48.8/1.7	8.85	61.0	8.85	61.0	0.0
25	50/49.5/0.5	8.81	60.4	8.80	60.3	0.1
	50/44/6	8.71	60.1	8.56	59.0	1.7
	50/40/10	8.52	58.7	7.98	55.0	6.3
	40/50/10	8.52	58.7	8.26	57.0	3.1
	40/48/12	8.44	58.2	8.02	55.3	5.0
30	50/39/11	8.47	58.4	7.75	53.4	8.5
	35/60/5	8.71	60.1	8.62	59.4	1.0
	30/65/5	8.67	59.8	8.53	58.8	1.6
	20/75/5	8.56	59.0	8.21	56.6	4.1
	60/35/5	8.71	60.1	8.40	57.9	3.6
35	65/30/5	8.66	59.7	8.04	55.4	7.2
	70/28/2	8.73	60.2	8.29	57.2	5.0

	74/24/2	8.65	59.6	7.83	54.0	9.5
C₄F₉OCH₃/t-DCE/ethanol (100°C)						
	54.4/44.7/0.9	87.56	604	87.56	604	0.0
5	54.8/45.1/0.1	87.49	603	87.48	603	0.0
	54/41/5	86.56	597	85.95	593	0.7
	50/45/5	86.64	597	86.28	595	0.4
	50/40/10	84.48	582	82.14	566	2.8
	40/50/10	84.63	584	83.25	574	1.6
10	30/60/10	84.10	580	82.38	568	2.0
	60/30/10	83.29	574	77.56	535	6.9
	60/28/12	81.89	565	73.80	509	9.9
	70/28/2	86.23	594	83.32	574	3.4
	74/24/2	85.30	588	80.14	553	6.0
15	50/46/4	86.98	600	86.79	599	2.2
	28/70/2	86.16	594	79.98	551	7.2
C₄F₉OCH₃/t-DCE/isopropanol (41.0°C)						
	52.0/46.7/1.3	14.74	102	14.74	102	0.0
20	70/29/1	14.60	101	14.29	102	2.1
	50/38/12	14.13	97.4	13.36	92.1	5.4
	29/70/1	14.41	99.4	13.46	92.8	6.6
	60/39.9/0.1	14.69	101	14.66	101	0.2
C₄F₉OCH₃/c-DCE/methanol (25°C)						
25	66.0/32.6/1.4	7.05	48.6	7.05	48.6	0.0
	66.7/33.2/0.1	7.00	48.3	7.00	48.3	0.0
	58/38/4	6.97	48.1	6.92	47.7	0.7
	56/40/4	6.97	48.1	6.91	47.6	0.9
30	60/30/10	6.69	46.1	6.32	43.6	5.5
	60/28/12	6.59	45.4	5.95	41.0	9.7
	70/28/2	7.04	48.5	7.02	48.4	0.3
	75/23/2	7.03	48.5	6.93	47.8	1.4
	80/18/2	6.97	48.1	6.61	45.6	5.2
35	82/16/2	6.94	47.8	6.36	43.9	8.4
	40/58/2	6.99	48.2	6.57	45.3	6.0

	39/59/2	6.99	48.2	6.41	44.2	8.3
C₄F₉OCH₃/c-DCE/ethanol (110°C)						
	66.3/32.8/0.9	98.76	681	98.76	681	0.0
5	66.7/33.2/0.1	98.68	680	98.68	680	0.0
	65.0/31.0/4.0	98.07	676	97.78	674	0.3
	60/30/10	95.20	656	93.09	642	2.2
	58/28/14	92.87	640	88.56	611	4.6
	70/18/12	91.62	632	82.88	571	9.5
10	80/19/1	97.48	672	93.94	648	3.6
	41/58/1	97.71	674	90.36	623	7.5
C₄F₉OCH₃/acetone/methanol (25°C)						
	80.4/14.3/5.3	4.04	27.9	4.04	27.9	0.0
15	82.6/16.4/1.0	3.94	27.2	3.93	27.1	0.3
	99/0.5/0.5	4.11	28.3	4.10	28.3	0.2
	50/40/10	4.21	29.0	4.17	28.8	1.0
	1/85/14	4.54	31.3	4.54	31.3	0.0
	90/1/9	3.98	27.4	3.96	27.3	0.5
20	60/20/20	3.91	27.0	3.77	26.0	3.5
	40/30/30	3.94	27.2	3.66	25.2	7.1
	20/50/30	4.20	29.0	3.99	27.5	5.0
	10/50/40	4.13	28.5	3.78	26.1	8.5
	10/60/30	4.30	29.6	4.13	28.5	4.0
25	1/98/1	4.47	30.8	4.46	30.8	0.2
C₄F₉OCH₃/acetone/ethanol (75°C)						
	85.1/11.1/3.8	23.11	159	23.11	159	0.0
	99/0.5/0.5	23.56	162	23.54	162	0.1
30	0.56/99/0.5	26.77	185	26.76	184	0.0
	80/5/15	22.19	153	21.58	149	2.7
	70/10/20	21.84	151	21.04	145	3.7
	60/20/20	22.47	155	21.86	151	2.7
	50/25/25	22.49	155	21.61	149	3.9
35	40/40/20	23.86	165	32.28	161	2.4
	30/60/10	25.34	175	25.05	173	1.1

	30/45/25	23.95	165	23.15	160	3.3
	30/40/30	23.35	161	22.25	153	4.7
	60/10/30	20.88	144	19.25	133	7.8
	20/50/30	24.04	166	23.03	159	4.2
5	10/60/30	24.64	170	23.74	164	1.0

C₄F₉OCH₃/acetone/isopropanol (75°C)

	86.7/11.8/1.5	22.86	158	22.86	158	0.0
	99/0.5/0.5	23.48	162	23.48	162	0.0
10	0.5/99/0.5	26.75	184	26.74	184	0.0
	80/5/15	21.76	150	21.12	146	2.9
	70/5/25	20.62	142	19.05	131	7.6
	60/10/30	20.37	140	18.66	129	8.4
	50/20/30	21.14	146	19.79	136	6.4
15	40/30/30	21.96	151	20.72	143	5.6
	30/40/30	22.74	157	21.55	149	5.2
	20/50/30	23.45	162	22.32	154	4.8
	10/60/30	24.08	166	23.03	159	4.4
	50/40/10	23.84	164	23.52	162	1.3
20	10/80/10	25.85	178	25.61	177	0.9

The results of this Example show that these compositions are azeotropic or azeotrope-like because when 50 wt.% of an original composition is removed, the vapor pressure of the remaining composition is within about 10% of the vapor pressure of the original composition, at a temperature of 25°C.

EXAMPLE 9

Impact of Vapor Leakage at 57.1°C

A leak test is performed on compositions of C₄F₉OCH₃ and methanol, at the temperature of 57.1°C. The results are shown below:

	Refrigerant	0 wt % evaporated		50 wt% evaporated		%
	<u>Weight Percent</u>	<u>Psia</u>	<u>kPa</u>	<u>Psia</u>	<u>kPa</u>	<u>Change</u>
	C ₄ F ₉ OCH ₃ /methanol					
5	93.5/6.5	14.72	101.5	14.72	101.5	0.0
	99/1	13.95	96.2	13.79	95.1	1.1
	80/20	14.04	96.8	13.52	93.2	3.7
	70/30	13.40	92.4	12.49	86.1	6.8
	65/35	13.09	90.3	12.08	83.3	7.7
10	60/40	12.80	88.3	11.75	81.0	8.2

These results show that compositions of C₄F₉OCH₃ and methanol are azeotropic or azeotrope-like at different temperatures, but that the weight percents of the components vary as the temperature is changed.

15

EXAMPLE 10

Refrigerant Performance

The following table shows the performance of various refrigerants. The data are based on the following conditions.

20

25	Evaporator temperature	40.0°F (4.4°C)
	Condenser temperature	110.0°F (43.3°C)
	Subcool	10.0°F (5.6°C)
	Return gas temperature	75.0°F (23.8°C)
	Compressor efficiency is 70%.	

25

The refrigeration capacity is based on a compressor with a fixed displacement of 3.5 cubic feet per minute and 70% volumetric efficiency.

30

Capacity is intended to mean the change in enthalpy of the refrigerant in the evaporator per pound of refrigerant circulated, i.e., the heat removed by the refrigerant in the evaporator per time. Coefficient of performance (COP) is intended to mean the ratio of the capacity to compressor work. It is a measure of refrigerant energy efficiency.

		Evap.		Cond.		Compr.		COP	Capacity	
		Press.		Press.		Disch. T.			Btu/min	kW
		Psia	kPa	Psia	kPa	(°F)	(°C)			
5	C ₄ F ₉ OCH ₃ /methanol									
	99/1	1.7	11	9.3	64	134.3	56.8	4.17	11.34	0.20
	95/5	2.1	15	11.8	81	146.2	63.4	4.17	14.57	0.26
	C ₄ F ₉ OCH ₃ /ethanol									
10	99/1	1.5	10	8.7	60	133.2	56.2	3.97	10.04	0.18
	95/5	1.7	12	9.7	67	140.1	60.1	4.07	11.54	0.20
	C ₄ F ₉ OCH ₃ /isopropanol									
	99/1	1.5	10	8.5	59	132.5	55.8	3.95	9.79	0.17
15	95/5	1.6	11	9.1	63	136.9	58.3	4.02	10.68	0.19
	C ₄ F ₉ OCH ₃ /n-heptane									
	99/1	1.4	10	8.1	56	131.6	55.3	3.94	9.24	0.16
	95/5	1.2	8	7.3	50	133.3	56.2	3.98	8.32	0.15
20	C ₄ F ₉ OCH ₃ /t-DCE									
	99/1	1.6	11	9.0	62	131.3	55.2	4.09	10.85	0.19
	55/45	4.0	28	19.3	133	168.9	76.1	4.09	25.06	0.44
25	C ₄ F ₉ OCH ₃ /c-DCE									
	99/1	1.6	11	8.8	61	131.6	55.3	4.04	10.46	0.18
	68/32	3.0	21	14.9	103	161.0	71.6	4.10	19.09	0.34
	C ₄ F ₉ OCH ₃ /acetone									
30	99/1	1.7	12	9.3	64	131.6	55.3	4.12	11.29	0.20
	85/15	2.9	20	14.8	102	146.8	63.8	4.11	18.61	0.33
	C ₄ F ₉ OCH ₃ /n-heptane/methanol									
	98/1/1	1.6	11	9.1	63	134.6	57.0	4.06	10.75	0.19
35	92/4/4	1.8	12	10.3	71	144.2	62.3	4.21	12.60	0.22

$C_4F_9OCH_3/t\text{-DCE/ethanol}$										
15	98/1/1	1.7	12	9.3	64	133.2	66.2	4.12	11.36	0.20
	60/35/5	3.5	24	17.4	120	177.4	80.8	4.21	23.13	0.41

$C_4F_9OCH_3/c\text{-DCE/methanol}$										
	98/1/1	1.8	12	9.8	68	134.7	57.1	4.13	11.91	0.21
	60/35/5	3.5	24	17.4	120	177.4	80.8	4.21	23.13	0.41

20

$C_4F_9OCH_3/c\text{-DCE/ethanol}$										
	98/1/1	1.6	11	9.2	63	133.5	56.4	4.07	10.95	0.19
	65/30/5	3.0	21	15.1	104	166.6	74.8	4.17	19.55	0.34

25	$C_4F_9OCH_3/acetone/methanol$									
	98/1/1	1.9	13	10.2	70	134.7	57.1	4.20	12.68	0.22
	80/10/10	3.3	23	17.1	118	166.2	74.5	4.27	22.46	0.40

$C_4F_9OCH_3/acetone/ethanol$										
30	98/1/1	1.8	12	9.6	66	133.5	56.4	4.14	11.76	0.21
	85/10/5	2.7	19	14.1	97	148.9	64.9	4.24	18.21	0.32

$C_4F_9OCH_3/acetone/isopropanol$										
	98/1/1	1.7	12	9.5	66	132.9	56.1	4.12	11.52	0.20
35	85/10/5	2.6	18	13.5	93	146.1	63.4	4.22	17.34	0.31

C₄F₉OCH₃/t-DCE/isopropanol

98/1/1	1.7	12	9.2	63	132.6	55.9	4.10	11.10	0.20
52/47/1	4.1	28	18.3	126	167.7	75.4	4.33	25.83	0.45

5 C₄F₉OCH₃/HFC-43-10mee/methanol

98/1/1	1.7	12	9.3	64	134.3	56.8	4.05	11.04	0.19
45/48/7	2.1	14	11.9	82	153.5	67.5	4.19	14.78	0.26

EXAMPLE 11**Heat Transfer Media**

Data below show heat transfer performance characteristics of compounds of the present invention. Pressure Drop Factor (Fp) is an indication of energy loss due to friction between fluid and pipe-wall with a low value being desirable. Heat Transfer Factor (Fh) is an indication of the ability of the fluid to transfer heat, with a high value desirable. Temperature Difference Factor (Fv) is a measure of the temperature change of the fluid in the process of transferring heat with a low value desirable. Pump Power Ratio is a comparison of the pumping energy with any one fluid. A lower value indicates less energy is required for pumping a given fluid.

20

<u>Compounds (wt. percents)</u>		<u>Pressure Drop Factor (Fp)</u>		
		<u>-40°F(-40°C)</u>	<u>0°F(-18°C)</u>	<u>40°F(4°C)</u>
	C ₄ F ₉ OCH ₃	0.0391	0.0346	0.0310
25	C ₄ F ₉ OCH ₃ /methanol (95/5)	0.0390	0.0344	0.0306
	C ₄ F ₉ OCH ₃ /ethanol (95/5)	0.0394	0.0346	0.0308
	C ₄ F ₉ OCH ₃ /isopropanol (95/5)	0.0396	0.0347	0.0310
	C ₄ F ₉ OCH ₃ /n-heptane (95/5)	0.0379	0.0336	0.0301
	C ₄ F ₉ OCH ₃ /c-DCE (68/32)	0.0368	0.0330	0.0298
30	C ₄ F ₉ OCH ₃ /acetone (85/15)	0.0354	0.0314	0.0282
	C ₄ F ₉ OCH ₃ /n-heptane/methanol (92/4/4)	0.0381	0.0336	0.0300
	C ₄ F ₉ OCH ₃ /n-heptane/ethanol (92/5/3)	0.0372	0.0348	0.0328
35	C ₄ F ₉ OCH ₃ /n-heptane/isopropanol (90/5/5)	0.0384	0.0337	0.0301

	C ₄ F ₉ OCH ₃ /c-DCE/methanol (60/35/5)	0.0366	0.0326	0.0294
	C ₄ F ₉ OCH ₃ /c-DCE/ethanol (65/30/5)	0.0372	0.0330	0.0297
	C ₄ F ₉ OCH ₃ /acetone/methanol (80/10/10)	0.0356	0.0312	0.0277
5	C ₄ F ₉ OCH ₃ /acetone/ethanol (85/10/5)	0.0369	0.0325	0.0290
	C ₄ F ₉ OCH ₃ /acetone/isopropanol (85/10/5)	0.0371	0.0326	0.0291
10	Heat Transfer Factor (Fh)			
	<u>Compounds (wt. percents)</u>	<u>-40°F(-40°C)</u>	<u>0°F(-18°C)</u>	<u>40°F(4°C)</u>
	C ₄ F ₉ OCH ₃	0.147	0.180	0.212
	C ₄ F ₉ OCH ₃ /methanol (95/5)	0.150	0.187	0.221
15	C ₄ F ₉ OCH ₃ /ethanol (95/5)	0.147	0.182	0.217
	C ₄ F ₉ OCH ₃ /isopropanol (95/5)	0.144	0.180	0.214
	C ₄ F ₉ OCH ₃ /n-heptane (95/5)	0.152	0.186	0.219
	C ₄ F ₉ OCH ₃ /c-DCE (68/32)	0.164	0.196	0.226
	C ₄ F ₉ OCH ₃ /acetone (85/15)	0.170	0.207	0.242
20	C ₄ F ₉ OCH ₃ /n-heptane/methanol (92/4/4)	0.154	0.190	0.225
	C ₄ F ₉ OCH ₃ /n-heptane/ethanol (92/5/3)	0.150	0.186	0.220
	C ₄ F ₉ OCH ₃ /n-heptane/isopropanol (90/5/5)	0.148	0.185	0.221
25	C ₄ F ₉ OCH ₃ /c-DCE/methanol (60/35/5)	0.168	0.203	0.236
	C ₄ F ₉ OCH ₃ /c-DCE/ethanol (65/30/5)	0.161	0.197	0.230
	C ₄ F ₉ OCH ₃ /acetone/methanol (80/10/10)	0.163	0.204	0.244
30	C ₄ F ₉ OCH ₃ /acetone/ethanol (85/10/5)	0.160	0.199	0.236
	C ₄ F ₉ OCH ₃ /acetone/isopropanol (85/10/5)	0.157	0.177	0.233

<u>Compounds (wt. percents)</u>		Temperature Difference Factor (Fv)		
		<u>-40°F(-40°C)</u>	<u>0°F(-18°C)</u>	<u>40°F(4°C)</u>
	C ₄ F ₉ OCH ₃	2.70	2.12	1.75
5	C ₄ F ₉ OCH ₃ /methanol (95/5)	2.63	2.04	1.67
	C ₄ F ₉ OCH ₃ /ethanol (95/5)	2.71	2.10	1.71
	C ₄ F ₉ OCH ₃ /isopropanol (95/5)	2.77	2.13	1.73
	C ₄ F ₉ OCH ₃ /n-heptane (95/5)	2.58	2.03	1.68
	C ₄ F ₉ OCH ₃ /c-DCE (68/32)	2.38	1.92	1.62
10	C ₄ F ₉ OCH ₃ /acetone (85/15)	2.26	1.79	1.49
	C ₄ F ₉ OCH ₃ /n-heptane/methanol (92/4/4)	2.56	1.99	1.63
	C ₄ F ₉ OCH ₃ /n-heptane/ethanol (92/5/3)	2.60	2.03	1.66
15	C ₄ F ₉ OCH ₃ /n-heptane/isopropanol (90/5/5)	2.66	2.05	1.67
	C ₄ F ₉ OCH ₃ /c-DCE/methanol (60/35/5)	2.32	1.85	1.55
	C ₄ F ₉ OCH ₃ /c-DCE/ethanol (65/30/5)	2.43	1.92	1.59
	C ₄ F ₉ OCH ₃ /acetone/methanol (80/10/10)	2.37	1.82	1.47
20	C ₄ F ₉ OCH ₃ /acetone/ethanol (85/10/5)	2.43	1.89	1.54
	C ₄ F ₉ OCH ₃ /acetone/isopropanol (85/10/5)	2.48	1.92	1.56

<u>Compounds (wt. percents)</u>		Pump Power Ratio		
		<u>-40°F(-40°C)</u>	<u>0°F(-18°C)</u>	<u>40°F(4°C)</u>
	C ₄ F ₉ OCH ₃	1.00	1.00	1.00
30	C ₄ F ₉ OCH ₃ /methanol (95/5)	0.92	0.87	0.84
	C ₄ F ₉ OCH ₃ /ethanol (95/5)	1.01	0.96	0.92
	C ₄ F ₉ OCH ₃ /isopropanol (95/5)	1.09	1.01	0.96
	C ₄ F ₉ OCH ₃ /n-heptane (95/5)	0.86	0.86	0.86
	C ₄ F ₉ OCH ₃ /c-DCE (68/32)	0.64	0.71	0.76
35	C ₄ F ₉ OCH ₃ /acetone (85/15)	0.54	0.55	0.57
	C ₄ F ₉ OCH ₃ /n-heptane/methanol (92/4/4)	0.83	0.80	0.78

	C ₄ F ₉ OCH ₃ /n-heptane/ethanol (92/5/3)	0.87	0.85	0.83
	C ₄ F ₉ OCH ₃ /n-heptane/isopropanol (90/5/5)	0.95	0.88	0.84
5	C ₄ F ₉ OCH ₃ /c-DCE/methanol (60/35/5)	0.59	0.62	0.65
	C ₄ F ₉ OCH ₃ /c-DCE/ethanol (65/30/5)	0.69	0.70	0.72
	C ₄ F ₉ OCH ₃ /acetone/methanol (80/10/10)	0.64	0.58	0.55
	C ₄ F ₉ OCH ₃ /acetone/ethanol (85/10/5)	0.69	0.66	0.64
10	C ₄ F ₉ OCH ₃ /acetone/isopropanol (85/10/5)	0.75	0.70	0.67

15 Data above show compounds of the present invention have heat transfer performance comparable to pure C₄F₉OCH₃ and are therefore suitable as heat transfer media.

The novel compositions of this invention, including the azeotropic or azeotrope-like compositions, may be used as cleaning agents to clean, for example, electronic circuit boards. It is preferred that cleaning agents be azeotropic or azeotrope-like because in vapor degreasing operations, the cleaning agent is generally redistilled and reused for final rinse cleaning. The novel compositions may also be used as displacement drying agents to remove water from surfaces.

25 The novel compositions of this invention, including the azeotropic or azeotrope-like compositions, may be used to produce refrigeration by condensing the compositions and thereafter evaporating the condensate in the vicinity of a body to be cooled. The novel compositions may also be used to produce heat by condensing the refrigerant in the vicinity of the body to be heated and thereafter evaporating the refrigerant.

The novel compositions of this invention are particularly suitable for replacing compounds that may affect the ozone layer, including R-113 and R-11.

30 In addition to cleaning and refrigeration applications, the novel constant boiling or substantially constant boiling compositions of the invention are also useful as aerosol propellants, heat transfer media, gaseous dielectrics, fire extinguishing agents, expansion agents for polyolefins and polyurethanes and power cycle working fluids.

ADDITIONAL COMPOUNDS

Other components, such as aliphatic hydrocarbons having a boiling point of about 0 to 100°C, hydrofluorocarbonalkanes having a boiling point of about 0 to 100°C, hydrofluoropropanes having a boiling point of between about 0 to 100°C, hydrocarbon
5 esters having a boiling point between about 0 to 100°C, hydrochlorofluorocarbons having a boiling point between about 0 to 100°C, hydrofluorocarbons having a boiling point of about 0 to 100°C, hydrochlorocarbons having a boiling point between about 0 to 100°C, chlorocarbons and perfluorinated compounds, can be added in small amounts to the
10 azeotropic or azeotrope-like compositions described above without substantially changing the properties thereof, including the constant boiling behavior, of the compositions.

Additives such as lubricants, corrosion inhibitors, surfactants, stabilizers, dyes and other appropriate materials may be added to the novel compositions of the invention for a variety of purposes provide they do not have an adverse influence on the composition for its intended application. Preferred lubricants include esters having a
15 molecular weight greater than 250.

2. A composition of matter comprising a compound selected from the group consisting of methanol, ethanol, isopropanol, n-heptane, trans-1,2-dichloroethylene, cis-1,2-dichloroethylene, acetone, and 1,1,1,2,3,4,4,5,5,5-decafluoropentane; nonafluoromethoxybutane, n-heptane and a compound selected from the group consisting of methanol, ethanol, and isopropanol; nonafluoromethoxybutane, trans-1,2-dichloroethylene and methanol, ethanol, or isopropanol; nonafluoromethoxybutane, cis-1,2-dichloroethylene and methanol or ethanol; nonafluoromethoxybutane, acetone and a compound selected from the group consisting of methanol, ethanol, or isopropanol; and nonafluoromethoxybutane, 1,1,1,2,3,4,4,5,5-decafluoropentane and methanol.

3. Effective amounts of the following compounds to form an azeotropic or azeotrope-like composition: nonafluoromethoxybutane and methanol, ethanol, isopropanol, n-heptane, trans-1,2-dichloroethylene, cis-1,2-dichloroethylene, or acetone, and 1,1,1,2,3,4,4,5,5,5-decafluoropentane; nonafluoromethoxybutane, n-heptane and methanol, ethanol, or isopropanol; nonafluoromethoxybutane, trans-1,2-dichloroethylene and methanol, ethanol, or isopropanol; nonafluoromethoxybutane, cis-1,2-dichloroethylene and methanol or ethanol; nonafluoromethoxybutane, acetone and methanol, ethanol or isopropanol; and nonafluoromethoxybutane, 1,1,1,2,3,4,4,5,5-decafluoropentane and methanol.

4. The azeotropic or azeotrope-like composition of claim 3, said composition consisting essentially of: 82-99 weight percent nonafluoromethoxybutane and 1-18 weight percent methanol; 75-99 weight percent nonafluoromethoxybutane and 1-25 weight percent ethanol; 64-99 weight percent nonafluoromethoxybutane and 1-36 weight percent isopropanol; 71-99 weight percent nonafluoromethoxybutane and 1-29 weight percent n-heptane; 31-78 weight percent nonafluoromethoxybutane and 22-69 weight percent trans-1,2-dichloroethylene; 44-85 weight percent nonafluoromethoxybutane and 15-56 weight percent cis-1,2-dichloroethylene; 1-99 weight

percent nonafluoromethoxybutane and 1-99 weight percent acetone; 80-99 weight percent nonafluoromethoxybutane, 0.5-18 weight percent n-heptane and 0.5-19 weight percent methanol; 75-99 weight percent nonafluoromethoxybutane, 0.5-24 weight percent n-heptane and 0.5-24 weight percent ethanol; 70-99 weight percent
5 nonafluoromethoxybutane, 0.5-29 weight percent n-heptane and 0.5-29 weight percent isopropanol; 20-74 weight percent nonafluoromethoxybutane, 24-75 weight percent trans-1,2-dichloroethylene and 0.5-12 weight percent methanol; 28-74 weight percent nonafluoromethoxybutane, 24-70 weight percent trans-1,2-dichloroethylene and 0.1-12 weight percent ethanol; 29-70 weight percent nonafluoromethoxybutane, 29-70 weight
10 percent trans-1,2-dichloroethylene and 0.1-12 weight percent isopropanol; 39-82 weight percent nonafluoromethoxybutane, 16-59 weight percent cis-1,2-dichloroethylene and 0.1-12 weight percent methanol; 41-80 weight percent nonafluoromethoxybutane, 19-58 weight percent cis-1,2-dichloroethylene and 0.1-14 weight percent ethanol; 0.5-99 weight percent nonafluoromethoxybutane, 0.5-99 weight percent acetone and 0.5-40 weight
15 percent methanol; 0.5-99 weight percent nonafluoromethoxybutane, 0.5-99 weight percent acetone and 0.5-30 weight percent ethanol; 0.5-99 weight percent nonafluoromethoxybutane, 0.5-99 weight percent acetone and 0.5-30 weight percent isopropanol and 20-75 weight percent nonafluoromethoxybutane, 20-70 weight percent acetone and 0.5-15 weight percent methanol.

20

5. A process for producing refrigeration, comprising condensing a composition of claim 2, and thereafter evaporating said composition in the vicinity of the body to be cooled.

25

6. A process for producing refrigeration, comprising condensing a composition of claim 3, and thereafter evaporating said composition in the vicinity of the body to be cooled.

30

7. A process for producing refrigeration, comprising condensing a composition of claim 4, and thereafter evaporating said composition in the vicinity of the body to be cooled.

35

8. A process for producing heat comprising condensing a composition of claim 2 in the vicinity of a body to be heated, and thereafter evaporating said composition.

11. A process for cleaning a solid surface which comprises treating said surface with a composition of claim 2.

10 12. A process for cleaning a solid surface which comprises treating said surface with a composition of claim 3.

13. A process for cleaning a solid surface which comprises treating said surface with a composition of claim 4.

15 14. A process for transfer of heat from a heat source to a heat sink with a composition of claim 2.

20 15. A process for transfer of heat from a heat source to a heat sink with a composition of claim 3.

16. A process for transfer of heat from a heat source to a heat sink with a composition of claim 4.

25 17. Effective amounts of nonafluoromethoxybutane and methanol, ethanol, isopropanol, n-heptane, trans-1,2-dichloroethylene, cis-1,2-dichloroethylene or acetone; nonafluoromethoxybutane, n-heptane and methanol, ethanol, or isopropanol; nonafluoromethoxybutane, trans-1,2-dichloroethylene and methanol, ethanol or isopropanol; nonafluoromethoxybutane, cis-1,2-dichloroethylene and methanol or ethanol;
30 nonafluoromethoxybutane, acetone and methanol, ethanol, or isopropanol; and nonafluoromethoxybutane, 1,1,1,2,3,4,4,5,5,-decafluoropentane and methanol to form binary or ternary compositions having a vapor pressure higher or lower than that of the components of the binary or ternary composition.

18. A process for producing refrigeration, comprising condensing a composition of claim 17, and thereafter evaporating said composition in the vicinity of the body to be cooled.

5 19. A process for producing heat comprising condensing a composition of claim 17 in the vicinity of a body to be heated, and thereafter evaporating said composition.

10 20. A process for cleaning a solid surface which comprises treating said surface with a composition of claim 17.

21. A process for transfer of heat from a heat source to a heat sink using a composition of claim 17.

INTERNATIONAL SEARCH REPORT

Inter. Appl. No.

PCT/US 97/01501

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 C09K5/04 C09K3/30 A62D1/00 C11D7/50 C23G5/028

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 C09K A62D C11D C23G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,Y	WO 96 22129 A (MINNESOTA MINING) 25 July 1996 see abstract; claims 1-3,7; example 1; table C ---	1-21
P,Y	WO 96 22356 A (MINNESOTA MINING) 25 July 1996 see abstract; claims 1,2,4; tables 1,3-12 ---	1-21
A	DE 12 94 949 A (FARBWERKE HOECHST) 17 May 1966 see the whole document -----	1-21



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"A" document member of the same patent family

Date of the actual completion of the international search

29 May 1997

Date of mailing of the international search report

13.06.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+ 31-70) 340-3016

Authorized officer

Nicolas, H

INTERNATIONAL SEARCH REPORT

information on patent family members

Inter. Appl. Application No

PCT/US 97/01501

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9622129 A	25-07-96	NONE	
WO 9622356 A	25-07-96	NONE	
DE 1294949 A		BE 690605 A	02-06-67
		CH 479514 A	15-10-69
		DE 1298514 B	
		DE 1301807 B	
		DE 1302054 B	
		FR 1506638 A	28-02-68
		NL 6616938 A	05-06-67

